



### SPECIFICATIONS

	UT306A
Temperature range	-35°C~300°C -31°F~572°F
Accuracy	≥0°C: ±2.0°C or ±2%; <0°C: ±(2.0°C+0.1°C/°C) ≥32°F: ±4.0°F or ±2%; <32°F: ±(4.0°F+0.1°F/°F)
D:S ratio	6:1
Response time	<250ms
Emissivity	0.95
Spectral response	8um~14um
Laser power	<1mW
<b>Features</b>	
Auto power off	√
Low battery indication	√
Data hold	√
°C/°F selection	√
MAX/MIN/AVG mode	√
Lock measurement	√
Backlight	√
Laser	√
Operating temperature	0°C~50°C (32°F~104°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90%RH (non-condensing)
Drop test	1m

UT306A is a portable non-contact thermometer. This device's miniature design is convenient to carry and suitable for everyday temperature measurement needs. UT306A is designed to counter environmental interference, ensuring accurate temperature readings under various measurement environments.

### GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	37.4mm x 36.4mm
Product color	Red and grey
Product net weight	120g
Product size	120mm x 53mm x 28mm
Standard accessories	Batteries
Standard individual packing	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	272mm x 225mm x 200mm
Standard carton gross weight	2.8kg